

UTI wooden back
5044-4LWW
Design mC.dsg



OUTDOOR FRAME
TELAIO OUTDOOR
BASTIDOR PARA
EXTERIORES

Metal frame in round tube diameter 16 mm, thickness 2 mm, accordingly with UNI EN 10305-3 rule in Asform.
Struttura in tubo tondo diametro 16 mm, spessore 2 mm, secondo norma UNI EN 10305-3 in Asform.
Bastidor metálico de tubo redondo de 16 mm de diámetro y 2 mm de espesor, conforme a la norma UNI EN 10305-3 en Asform.

1032F-E	7016F-E	1019F-E	7035F-E	3009F-E	6013F-E	20-E
ROVAN	ROTA28	ROTA04				

BACKREST
BACKREST
RESPALDO

FINISHING
FINITURA
ACABADO

Painted frame with epoxy-polyester powder with average thickness of 50 µ.
Verniciatura a polveri epossipoliesteri spessore medio di 50 µ.
Bastidor con recubrimiento en polvo epoxipoliéster con 50 µ de espesor medio.

FEET
PIEDINI
PIES DE APOYO

Polypropylene.
Polipropilene
Polipropileno

OPTIONAL
OPTIONAL
OPTIONAL

Polyurethane foam seat, upholstered.
Seduta in poliuretano espanso, imbottito.
Asiento de espuma de poliuretano, tapizado.

Reproduction of this document is strictly prohibited without prior written authorisation from Omip srl. Sizes, weights and finishes may change without previous notice.
È vietata la riproduzione del seguente documento senza previa autorizzazione scritta da parte di Omip srl. Dimensioni, pesi e finiture possono variare senza alcun preavviso.
La reproducción de este documento está estrictamente prohibida sin la autorización previa de Omip srl. Los tamaños, pesos y acabados pueden cambiar sin previo aviso.

UTI wooden back with arms
5044-4WCW
Design mC.dsg



OUTDOOR FRAME
TELAIO OUTDOOR
BASTIDOR PARA
EXTERIORES

Metal frame in round tube diameter 16 mm, thickness 2 mm, accordingly with UNI EN 10305-3 rule in Asform.
Struttura in tubo tondo diametro 16 mm, spessore 2 mm, secondo norma UNI EN 10305-3 in Asform.
Bastidor metálico de tubo redondo de 16 mm de diámetro y 2 mm de espesor, conforme a la norma UNI EN 10305-3 en Asform.

						
1032F-E	7016F-E	1019F-E	7035F-E	3009F-E	6013F-E	20-E
						
ROVAN	ROTA28	ROTA04				

BACKREST
BACKREST
RESPALDO

FINISHING
FINITURA
ACABADO

Painted frame with epoxy-polyester powder with average thickness of 50 µ.
Verniciatura a polveri epossipoliesteri spessore medio di 50 µ.
Bastidor con recubrimiento en polvo epoxipoliéster con 50 µ de espesor medio.

FEET
PIEDINI
PIES DE APOYO

Polypropylene
Polipropilene
Polipropileno

OPTIONAL
OPTIONAL
OPTIONAL

Polyurethane foam seat, upholstered.
Seduta in poliuretano espanso, imbottito.
Asiento de espuma de poliuretano, tapizado.

Reproduction of this document is strictly prohibited without prior written authorisation from Omip srl. Sizes, weights and finishes may change without previous notice.
È vietata la riproduzione del seguente documento senza previa autorizzazione scritta da parte di Omip srl. Dimensioni, pesi e finiture possono variare senza alcun preavviso.
La reproducción de este documento está estrictamente prohibida sin la autorización previa de Omip srl. Los tamaños, pesos y acabados pueden cambiar sin previo aviso.